

Adj. plug for square pipe 30x30x1,5-2 8k

Article Number: 300011673




Technical Data

Attribute	Value
RoHS	RoHS compliant
Colour	black
Country of origin	Germany
Customs tariff number	39235010
Material	PA
Previous part number	0603030
Weight	12,65 g
External pipe dimension	30 mm
Max. load capacity	300 kg
Pipe wall thickness	1,5 - 2,0 mm
Shape	square
Thread length	25,0 mm
Thread size	M22
Thread type	integrated
Version	with adjustment screw
Width across flat	28

Description

One-piece external body with injection-moulded thread. Octagonal screw head (except 0602020 + 0602222, hexagonal) Axial load capacity: M10 = approx. 100 kg / M16 = approx. 150 kg / >M22 = approx. 300 kg Load capacity: - The adjustment of the feet has to be effected unloaded - The axial static load indicated refers to a screw that is unscrewed by 10 mm and is seated on plane ground - The adjustable plugs are unsuitable to be used as load gliders - The adjustable plugs are not suitable for dynamic load

Drawing and Dimension Table



Attribute	Value
AxS	30x30x1,5-2 mm
M x L	M22x25 mm
SW	28



Scan the QR code to discover more items in this category.

For personalized advice, feel free to contact us at sales@emico.com or by phone at +49 9621 67545-0.

The information in this document is provided to the best of our knowledge, but without guarantee. Changes and errors reserved.